

Vermeer®

Hydrostatic Trencher

T1055



COMMANDER®

COMMANDER[®]

T1055

Unmatched Performance

On jobsites around the world, contractors depend on one name for heavy-duty rock trenching: Vermeer[®]. For projects requiring high horsepower and deep digging depths, Vermeer offers the T1055 COMMANDER[®] 3. Powered by a Caterpillar C13 ACERT Tier 3 engine generating 415 hp (309.5 kW), the T1055 features a Rotary Power headshaft motor to produce high torque for tough trenching situations.

Smart Features

The T1055 is equipped with the new TEC[®] Plus electronic control system, designed for improved diagnostic capabilities and to increase performance by enhancing machine controllability. Additionally, a standard, pressurized and climate-controlled cab enhances operator comfort and is elevated for exceptional visibility.

For maximum versatility, the T1055 COMMANDER 3 tractor unit is also available with the Terrain Leveler[®] surface excavation attachment for site prep, surface mining and soil remediation applications.

Maximum Rock-Trenching Muscle



Sectionalized boom lengths increase work efficiency. The 6', 8', 10', 12' or 14' (1.8 m, 2.4 m, 3 m, 3.7 m or 4.3 m) boom lengths offer job flexibility and eliminate the time and effort of changing booms.

Hydrostatic Trencher



A 415 hp (309.5 kW) Caterpillar Tier 3 engine provides the raw power needed to triumph over tough rock-trenching projects. The engine is emissionized and features high torque rise, allowing engine rpm to recover rapidly in situations that demand increased power.



A Rotary Power headshaft and splined headshaft produce lower speed and higher torque, providing superior rock penetration and low chain wear for better production results.



The new TEC Plus electronic control system features CAN bus technology, which utilizes multiple control modules located throughout the machine for real-time performance data and advanced troubleshooting capabilities.

T1055 COMMANDER 3 Specifications

Transport Dimensions

Approach angle: 16°
Height: 11.3' (3.4 m)
Length with 40" (101.6 cm) end idler and 6' (1.8 m) boom: 32' (9.8 m)
Length with 40" (101.6 cm) end idler and 8' (2.4 m) boom: 35' (10.7 m)
Length with 40" (101.6 cm) end idler and 10' (3 m) boom: 37' (11.3 m)
Length with 40" (101.6 cm) end idler and 12' (3.7 m) boom: 40' (12.2 m)
Length with 40" (101.6 cm) end idler and 14' (4.3 m) boom (with restraint bar): 41' (12.5 m)
Length with 50" (127 cm) end idler and 10' (3.1 m) boom: 36' (11 m)
Length with 50" (127 cm) end idler and 12' (3.7 m) boom: 38' (11.6 m)
Length with 50" (127 cm) end idler and 14' (4.3 m) boom (with restraint bar): 41' (12.5 m)
Weight range: 87,000 lb – 104,000 lb (39,462.5 kg – 47,173.6 kg)
Width: 116" – 122" (294.6 – 309.9 cm)

Engine

Make and model: Caterpillar C13 ACERT Tier 3
Gross horsepower: 415 hp (309.5 kW)
Rated engine rpm: 2100
Number of cylinders: 6
Fuel tank capacity: 184 gal (696.5 L)
Operating range: 8.8 hr
Fuel consumption @ full load: 20.9 gph (79 L/h)
Max engine operating angle: 35°
Air cleaner: Dry-type exhaust-aspirated
Aspiration: Turbocharged and air-to-air aftercooled (ATAAC)
Cooling medium: Liquid
Electrical system: 24 V DC
Oil filter: Full-flow

Tracks

Auto self-level: No
Ground pressure: 9.4 – 14 psi (.6 – 1 bar)
Tilt track available: No
Track drive type: Dual-path hydrostatic with planetary transmission
Track length: 14.7' (4.5 m)
Track pad type: Single, double or triple grouser
Track pad width: 24" or 30" (61 cm or 76.2 cm)
Track size: D7G
Travel speed max (high range): 114 fpm (34.8 m/min)
Travel speed max (low range): 57 fpm (17.4 m/min)
Parking and emergency brake: Spring-applied, hydraulic release, wet disc brake
Service brakes: Hydrostatic

Cab

Air conditioner / heater: Standard
Air suspension seat: No
AM / FM stereo with weather band: Standard
Elevating: Standard
Pressurized / filtered air: Standard
Roll Over Module (ROM): Standard
Control system: TEC Plus

Conveyor

Belt width: 30" (76.2 cm)
Conveyor belt speed range: 0 – 1070 fpm (0 – 326.1 m/min)
Conveyor belt style: Cleat or finger type
Conveyor length: 108" or 168" (274.3 cm or 426.7 cm)
Conveyor shift available: Yes
Conveyor shift distance: 5" or 65" (12.7 cm or 165.1 cm)
Conveyor style: Curved
Discharge direction: Right or left
Discharge height: 62" or 78" (157.5 or 198.1 cm)

Hydraulic System

Oil tank capacity: 152 gal (575.4 L)
Oil type: Vermeer HyPower 68 or HyPower 100
Pressure setting: 2500 psi (172.4 bar)
Pump flow max: 28 gpm (106 L/min)
Type: Pressure and flow compensated (load sensing)

Trencher Attachment

Boom depth options: 6', 8', 10', 12', 14' (1.8 m, 2.4 m, 3 m, 3.7 m, 4.3 m)
Sectionalized boom: Yes
Boom top rollers: Optional
Chain speed range: 316 – 714 fpm (96.3 – 217.6 m/min)
Cutting width range: 26" – 42" (66 cm – 106.7 cm)
Digging chain size: 4501 double, 5501 double, D6 double
Idler diameter: 40" or 50" (101.6 - 127 cm)
Trencher drive type: 2 pumps and 1 motor hydrostatic

Terrain Leveler Surface

Excavation Attachment

Weight: 40,000 lb (18,143.7 kg)
Max cutting depth: 32" (81.3 cm)
Cutting width: 11' (3.4 m)
Drum speed: 29-59 rpm
Laser acceptable: Yes
Digging chain size: Double 4501
Drive type: 2 pumps and 1 motor hydrostatic



The Vermeer dealer network: Reliable support, all over the world.



With nearly 200 locations across the globe - you're never far from an independent, authorized Vermeer dealer. Our dealers are in place to support your success with product expertise that's second to none.



When you need service, you can count on your local Vermeer dealer. With multiple locations, remote service trucks, and factory-offered technician training, your local Vermeer dealer offers reliable service that keeps your equipment running.



Vermeer parts are designed and manufactured to original specifications, so whether they're new parts or replacement parts, they'll live up to the Vermeer name.



Vermeer EMEA
(Europe, Middle East, Africa and CIS)
P.O. Box 323
4460 AS Goes
the Netherlands
Phone: +31 113 272700
Fax: +31 113 272727

Vermeer Corporation
1210 Vermeer Road East
P.O. Box 200
Pella, Iowa 50219 U.S.A.
Phone: (641) 628-3141
Fax: (641) 621-7773
International fax: +1 (641) 621-7730
www.vermeer.com

Vermeer Asia Pacific
48 Toh Guan Road East
#01-105 Enterprise Hub
Singapore 608586
Phone: +65 6516 9560
Fax: +65 6515 9218

Call toll-free 1-888-VERMEER
1-888-837-6337 (USA only)

Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information about machine specifications. Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Vermeer, the Vermeer logo, Commander, Terrain Leveler, and TEC are trademarks of Vermeer Manufacturing Company in the U.S. and / or other countries. Cat is a trademark of Caterpillar, Inc. Rotary Power is a trademark of Rotary Power, Inc. © 2010 Vermeer Corporation. All Rights Reserved.