



ROBUST CUTTING POWER. The SC382 is equipped with a 37 hp (27.6 kW) Briggs and Stratton Vanguard engine, giving you power straight to the stump.



STANDARD FOUR WHEEL DRIVE. Four-wheel drive comes standard on the SC382. It offers traction and maneuverability in difficult transport conditions.



OPTIMIZED WHEEL. The SC382 stump cutter wheel has an optimized profile and tooth pattern to help with productivity and chip flow of recirculating material.



OPTIONAL HYDRAULIC PUSH BLADE. The optional hydraulic push blade on the SC382 simplifies jobsite cleanup by helping maneuver processed material.



OPERATOR PRESENCE SYSTEM. The dual-axis joystick control handles for boom swing, boom raise/lower and machine propel are equipped with an operator presence feature. This user-friendly operator presence system is intended to enhance operator safety.



SMARTSWEEP™ CONTROL SYSTEM. The patented SmartSweep™ control system monitors engine speed and automatically adjusts cutter wheel sweep rate to maximize power to the cutter wheel while reducing engine stress.



DO MORE.

Vermeer









SC382 STUMP CUTTER

GENERAL WEIGHTS AND DIMENSIONS

Length: 118" (299.7 cm)

Width (with duals): 49.6" (126 cm)
Width (without duals): 35.5" (90.2 cm)

Height: 53" (134.6 cm)

Weight (no blade): 1835 lb (832.3 kg)

Type: Rubber tire self-propelled

Maximum Ground speed: 65 fpm (19.8 m/min) to 130 fpm (39.6 m/min)

ENGINE

Make and model: Briggs & Stratton Vanguard

Gross horsepower: 37 hp (27.6 kW) Max torque: 49 ft-lb (66.4 Nm)

Number of cylinders: 2

Fuel type: Gasoline Cooling medium: Air

CUTTING DIMENSIONS

Cutter wheel straight line dimension: 47" (119.4 cm)

Cutter wheel cut above ground: 24" (61 cm)
Cutter wheel cut below ground: 15" (38.1 cm)

CUTTER WHEEL

Cutter wheel diameter (without teeth): 17" (43.2 cm)

Cutter wheel thickness: .5" (12.7 mm)

Tooth style: Yellow Jacket Cutter System

Number of teeth: 20

Chip containment: 7.5 cu ft (.2 m3)

CAPACITIES/ELECTRICAL

Fuel tank capacity: 10 gal (22.7 L) Hydraulic tank: 6.5 gal (24.6 L)

Pump flow at max rpm: 6.4 gpm (16L/min)

Electrical system: 12 V

OPTIONS

Hydraulic front blade

Extended warranty

Special paint

Planned maintenance

Vermeer Confidence Plus® asset protection program

NOTES:	

Vermeer

EQUIPPED TO

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Firestick and Navigator are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Aurora is a registered trademark of Digital Control Incorporated. John Deere is a registered trademark of Deere & Company. © 2019 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.